


8% Oxygen / Nitrogen



TIGCS delivers mixed calibration gases in a mode of supply to suit each of our customer's needs: cylinder or mixed onsite

● Applications

Oxymitter gas calibration for flu gas measurement, control oxygen in furnace or boiler

● Transport information

Compressed gas

Proper shipping name O2 8%;N2 92%
UN Nr 1956
ADR/RID Class 2 Label 2.2



● Safety Data sheets

Access:

● Physical information

Molecular weight 28.33 g/mol
Vapor density, gas 0.98 (air=1)
Colour colourless gas
Odor none

● Properties

Hazards identification: Gas/vapor heavier than air.
May accumulate in confined spaces, particularly at or below ground level
Contains gas under pressure; may explode if heated
May displace oxygen and cause rapid suffocation

● Cylinder equipment

Valve: CGA 540
Cylinder color: Gray
Cylinder strip: Black



● Product Specification

Components (% Vol. abs)	Impurities (ppm v/v)	Supply mode	Packaging size	Pressure (bar)	*Capacity (m3)
O2 8% ± 0.8%	H2O ≤ 5	Cylinder	47L	150	7
N2 balance		Cylinder	50L	200	10
		Pack 16	50L	200	162

*Typical capacities of the product are guaranteed for each cylinder in particular.

DISCLAIMER

The information contained in this Product Sheet is of a general nature and does not take into account any specific or local condition or regulation and shall neither be considered as recommendations. TIGCS assumes no liability or responsibility regarding the information contained in this Product Sheet, the completeness of this document, for the use of the information or consequences of such use, and disclaims all warranties (direct or indirect) of any kind.